



DATA SHEET FICHA TECNICA

NAME OF SERIES OR ITEM NUMBER	PKPV12118LZ2
MATERIAL	PVC
GROSOR	5mm
CAPA DE USO	0.5 mm
DIMENSIONES	1219.2x183
TIPO	LVT CLICK
ACABADO	MATE PROTECCION UV DEEP WOOD

PRUEBA	TEST ITEM	TEST METHOD	REQUIREMENT	TEST RESULT	VERDICT
DIMENSIONES	SIZE	ASTM F2055-10	Length: 1219.2±2.36mm Width:184.15±0.30mm	Length: 1219.2mm Width:184.15mm	PASS
ESPESOR	THICKNESS	ASTM F386-11	5±0.26mm	Average:5.mm Min:4.9mm Max:5.1mm	PASS
RECTANGULARIDAD	SQUARENESS	ASTM F2055-10	≤0.25mm	Deviation range: 0.03mm~+0.09mm	PASS
DUREZA DE INDENTACION	RESIDUAL INDENTATION	ASTM F1914-07	Average value:≤8% Maximum value: ≤10%	Average:0.6% Min:0.4% Max:0.65%	PASS
ESTABILIDAD DIMENSIONAL	DIMENSION STABILITY	ASTM F2199-09	≤0.51mm/305mm	Length Direction:- 0.04% Width Direction:-0.02%	PASS
RESISTENCIA A QUIMICOS	RESISTANCE TO CHEMICALS	ASTM 925-13	No more than a slight change in surface dulling, surface attack or staining	Rating 0: No change	PASS
RESISTENCIA AL CALOR	RESISTANCE TO HEAT	ASTM F1514-03	Average ΔE*ab ≤ 8.0	Average ΔE*ab: 0.66	PASS
RESISTENCIA A LA LUZ	RESISTANCE TO LIGHT	ASTM F1515-15	Average ΔE*ab ≤ 8.0	Average ΔE*ab: 1.7	PASS

SIZE FORMATO	M2/BOX M2/CNT	PCS./BOX PZA./CAJA	BOX/PALLET CAJA/PALETA	M2/PALLET M2/PALETA	KG/BOX KG/CAJA	KG/PALLET KG/PALETA
1219.0x183X5MM	1.785	8	60	98.17	18	1080