


Ceramic tile laying jobs may sometimes be quite delicate with problems which differ from standard applications such as linear wall tiling. Stairs, for instance, to be covered with the same tiles as the floor may require non standard spacing to match different heights from step to connecting floor for example.

The STAIRTEC product range is conceived to face these adjustment problems by featuring valid and lasting technical solutions.

stairtec™ FSF




This is the section for H 8 and 10 mm. For H 12,5 mm the section is different

Illustrated scale dimension 1:1



The product FSF is certified R10.
Anti-slip properties. According to standard DIN 51130 (06/2004).



STAIRTEC FSF-A* Aluminium + Synthetic insert width 30 mm
Base profile in aluminium with an anti-slip synthetic insert strip already mounted which can be replaced in case of damage or wear.
End caps FST available for each height 8 / 10 / 12,5 mm.

	H=mm		Art.		Insert Colours
Material:	8	FSF	80	A*	23/32/51
Extruded Natural aluminium	10	FSF	100	A*	23/32/51
Synthetic Insert	12,5	FSF	125	A*	23/32/51
Length: 2,70 metres					
Width: 30 mm					
Colours*: Grey (23), Beige (32), Black (51)					

Material:	8	FST	80	P*	23/32/51
PVC	10	FST	100	P*	23/32/51
Colours*: Grey (23), Beige (32), Black (51)	12,5	FST	125	P*	23/32/51

